

1941

Rigidity Modulus of Lead Single Crystals (Abstract)

Irvin H. Swift
State University of Iowa

Copyright © Copyright 1941 by the Iowa Academy of Science, Inc.
Follow this and additional works at: <https://scholarworks.uni.edu/pias>

Recommended Citation

Swift, Irvin H. (1941) "Rigidity Modulus of Lead Single Crystals (Abstract)," *Proceedings of the Iowa Academy of Science*: Vol. 48: No. 1 , Article 90.
Available at: <https://scholarworks.uni.edu/pias/vol48/iss1/90>

This Research is brought to you for free and open access by UNI ScholarWorks. It has been accepted for inclusion in Proceedings of the Iowa Academy of Science by an authorized editor of UNI ScholarWorks. For more information, please contact scholarworks@uni.edu.

INTERPRETATION OF VARIATION OF PARTIAL MOLAL
VOLUME OF THE SOLUTE WITH AQUEOUS SOLUTIONS
OF STRONG ELECTROLYTES

(ABSTRACT)

G. W. STEWART

One view is that the variation in the partial molal volume of water is produced by a change in its structure from a four-coordinated to a higher one. This view receives corroboration from experiments with the x-ray diffraction pattern of aqueous ionic solutions of thirty-one strong electrolytes. The results show a correspondence between the rate of variation of (1) the partial molal volume with concentration of the electrolyte; and (2) the liquid structure of the water also with concentration.

STATE UNIVERSITY OF IOWA,
IOWA CITY, IOWA.

RIGIDITY MODULUS OF LEAD SINGLE CRYSTALS

(ABSTRACT)

IRVIN H. SWIFT

The isothermal rigidity modulus has been measured for lead crystals of various orientations. The reciprocal bending-torsion effect and its influence on the measurement are considered.

STATE UNIVERSITY OF IOWA,
IOWA CITY, IOWA.

AN ELECTRICAL CIRCUIT DESIGNED FOR USE IN A
CALCULATING INSTRUMENT

(ABSTRACT)

RAY WENDLAND

Mathematical analysis of the potential variation produced by a circuit comprising two slide wire resistors (potentiometers) linked in parallel revealed the possibility of compensating the circuit so as to provide a potential varying as the product of the resistances in the individual slide wires. The problem was to counteract the fall in potential produced when a resistor is placed across a potentiometer circuit delivering an initial potential, E_0 .