

Proceedings of the Iowa Academy of Science

Volume 35 | Annual Issue

Article 54

1928

Visible Phase Relations in an A.C. Circuit

L. B. Spinney

Copyright ©1928 Iowa Academy of Science, Inc.

Follow this and additional works at: <https://scholarworks.uni.edu/pias>

Recommended Citation

Spinney, L. B. (1928) "Visible Phase Relations in an A.C. Circuit," *Proceedings of the Iowa Academy of Science*, 35(1), 254-254.

Available at: <https://scholarworks.uni.edu/pias/vol35/iss1/54>

This Research is brought to you for free and open access by the Iowa Academy of Science at UNI ScholarWorks. It has been accepted for inclusion in Proceedings of the Iowa Academy of Science by an authorized editor of UNI ScholarWorks. For more information, please contact scholarworks@uni.edu.

These carbons are connected to a 110-volt circuit with a resistance of 5 to 10 ohms, more or less, in series. If now the gap between the upper ends of the carbons is momentarily bridged by another carbon rod, an arc will form and remain when the short-circuiting carbon rod is removed.

If alternating current is used the carbons burn down equally. On direct current the consumption of the positive carbon is more rapid than that of the negative. This effect may be offset in a measure by the use of carbons of different size, or in some cases by use of a reversing switch by means of which the polarity of the carbons may be changed from time to time.

VISIBLE PHASE RELATIONS IN AN A. C. CIRCUIT

L. B. SPINNEY

By connecting low wattage neon lamps in parallel with the different portions of an alternating current circuit the phase differences in these parts may be made visible by the rise and fall of the glow in the corresponding lamps.

The lamps used for this purpose are those in which the glow appears upon the lamp terminals or electrodes and the phase difference in the glow of the different lamps is made visible by viewing the lamps through radial slots in a revolving disc. If the speed of the disc is properly adjusted the phase differences are readily observed.

PHOTOMOGRAPH

L. B. SPINNEY

A photometer is arranged in such manner that the screen and the lamp tested are stationary, the standard lamp being adjusted in distance to effect a balance. If the standard is moved by means of a band running over a wheel conveniently near the screen this wheel will revolve through an angle proportional to the distance the standard is moved. A spiral may now be drawn upon the face of the wheel of the form $p = a\Theta^{-2}$, where p is the radius vector and Θ the angle through which the spiral-wheel turns, such that p at any point is proportional to the corresponding illumination of the screen and therefore also to the candle power of the tested lamp. A candle power scale of equal scale divisions may be placed opposite the spiral for reading off the candle power directly, or the spiral