Proceedings of the Iowa Academy of Science

Volume 34 | Annual Issue

Article 80

1927

Thermo-Electric Effect in Single Crystal Zinc

Ernest G. Linder
State University of Iowa

Let us know how access to this document benefits you

Copyright ©1927 Iowa Academy of Science, Inc.

Follow this and additional works at: <https://scholarworks.uni.edu/pias>

Recommended Citation

Linder, Ernest G. (1927) "Thermo-Electric Effect in Single Crystal Zinc," *Proceedings of the Iowa Academy of Science*, 34(1), 278-279.

Available at: <https://scholarworks.uni.edu/pias/vol34/iss1/80>

This Research is brought to you for free and open access by the Iowa Academy of Science at UNI ScholarWorks. It has been accepted for inclusion in Proceedings of the Iowa Academy of Science by an authorized editor of UNI ScholarWorks. For more information, please contact scholarworks@uni.edu.

precautions had to be observed in the taking of this particular type of data.

IOWA STATE COLLEGE,
AMES, IOWA.

CORRELATION OF NEATNESS AND SCHOLARSHIP IN PHYSICS

GEORGE E. DAVIS

353 reports, written by 33 students in three laboratory sections of junior physics, were graded as to neatness. The average neatness grade and the term laboratory grade for each student were used in a correlation study. For each of the three laboratory sections the correlation coefficient was positive. The coefficient for all 33 students was $+0.27$.

Although the number of students graded was small, we may conclude that in general we may expect neatness and high grades in physics to be associated. Exceptions to the rule and a low correlation coefficient both definitely indicate that neatness of written reports can not alone be relied upon as an index of scholarship in physics.

THERMO-ELECTRIC EFFECT IN SINGLE CRYSTAL ZINC

ERNEST G. LINDER

Data are presented on the thermal e.m.f. against copper of six single crystal wires of zinc, of which the orientations of the main crystallographic axis with respect to the wire axis, range from 11.4° to 90° . The temperature interval is from -182° to 475° C.

From the data are calculated the thermo-electric power, Peltier coefficient, and difference of the Thomson coefficients for Zn against Zn. The data also provide a test for the Voigt-Thomson law for the variation of the thermo-electric power with crystal orientation. The law is verified for the low temperatures, but the deviations at the high temperatures ($300^\circ - 400^\circ$) are greater than the experimental errors are thought to be.

The thermo-electric powers of liquid zinc against solid single crystal zinc of different orientations, and against polycrystalline zinc are given, the value $-7.89/\text{deg.}$ for $(e_1 - e_s)$ for polycrystalline zinc having been found.

A theoretical expression is derived for the thermo-electric power of polycrystalline zinc in terms of the principal thermo-electric powers of the component crystals.

STATE UNIVERSITY OF IOWA,
IOWA CITY, IOWA.

A MICROPHOTOMETER FOR THE STUDY OF SPECTOGRAMS

I. J. GWINN

A modification of Harrison's microphotometer has been developed, following his suggestion, which is used for accurate measurements of line widths on spectrograms. A vertical optical system using microscope lenses focuses the light on a bismuth-silver thermocouple. Accurate readings of length are obtained with a finely constructed micrometer screw.

Studies have also been made on the relative intensities of lines on both optical and X-ray spectrograms. The instrument is also of use in testing the uniformity of thin films of metal.

STATE UNIVERSITY OF IOWA,
IOWA CITY, IOWA.

A SPECTROPHOTOMETRIC METHOD OF STUDYING HEMOGLOBIN AND OTHER COLORED SUB- STANCES IN SOLUTION

GEORGE E. DAVIS

An investigation was carried out to determine the possibilities of applying spectrophotometric methods to the problem of estimating the concentration of hemoglobin in blood. The concentration of a substance in solution can easily be determined from its transmission of some particular wave length, providing the absorption ratio for that wave length is known. A late model direct reading spectrophotometer was used. The method was found to be fairly accurate and simple and should prove valuable in other physical investigations involving the study of spectral transmission curves of various colored substances.

Some interesting irregularities in the shape of the spectral transmission curve in one of the absorption bands of oxyhemoglobin were observed.

These investigations were carried out under the direction of