

1925

## The Position of the Vibrating Source in the Kundt's Tube Experiment

G. W. Stewart  
*State University of Iowa*

*Let us know how access to this document benefits you*

Copyright ©1925 Iowa Academy of Science, Inc.

Follow this and additional works at: <https://scholarworks.uni.edu/pias>

---

### Recommended Citation

Stewart, G. W. (1925) "The Position of the Vibrating Source in the Kundt's Tube Experiment," *Proceedings of the Iowa Academy of Science*, 32(1), 383-383.

Available at: <https://scholarworks.uni.edu/pias/vol32/iss1/88>

This Research is brought to you for free and open access by the Iowa Academy of Science at UNI ScholarWorks. It has been accepted for inclusion in Proceedings of the Iowa Academy of Science by an authorized editor of UNI ScholarWorks. For more information, please contact [scholarworks@uni.edu](mailto:scholarworks@uni.edu).

THE ACTION OF CYLINDRICAL TUBES IN BRANCH  
ACOUSTIC LINES

G. W. STEWART

*(ABSTRACT)*

Quincke's tube has long been known. A theoretical and experimental study of its action is herewith reported. Also the formulas for an open tube as well as a closed tube have been derived. The experimental results show unmistakable evidence of the viscosity. The selective property of Quincke's tube is ascertained both experimentally and theoretically for the first time.

STATE UNIVERSITY OF IOWA.

THE POSITION OF THE VIBRATING SOURCE IN THE  
KUNDT'S TUBE EXPERIMENT

G. W. STEWART

*(ABSTRACT)*

Various textbooks are not in agreement as to whether the vibrating piston is at a node or "near a node." The theory shows that it is strictly at a node. The misstatement in regard to the location of the piston has probably been caused by a misunderstanding of the word "node." The piston is one-half wave-length from the nearest node and yet it is strictly not a point of rest.

STATE UNIVERSITY OF IOWA

THE ACTION OF AN ORIFICE IN AN ACOUSTIC CON-  
DUIT AND A MEANS OF DETERMINING THE  
EFFECT OF VISCOSITY

G. W. STEWART

It was shown in a previous communication that the transmission through an acoustic conduit could be computed if the components of the impedance of the branch line were known. In the case of the orifice when viscosity is considered the following are the values of the two components:

$$Z = \rho k^2 a / 2\pi + (2\omega \rho \mu)^{\frac{1}{2}} (\pi R^3)^{-1} L,$$

$$Z = \rho \omega / c + (2\omega \rho \mu)^{\frac{1}{2}} (\pi R^3)^{-1} L.$$

An experimental and theoretical study has been made of orifices